



BEACON

WATER TECHNOLOGIES

Pile Cloth Disk Filtration Systems



GDisk® Models

Available in five different models, all offered in concrete and package stainless steel (304SS or 316SS).




Model	Disk Diameter	Max Capacity /Unit*	Segments/Disk	Max # Disks/Unit
GDisk®-Giant	9.8 ft (3.0 m)	25.4 MGD	8	24
GDisk®-Standard	7.2 ft (2.2 m)	12.7 MGD	6	24
GDisk®-Compact	5.9 ft (1.8 m)	8.22 MGD	6	24
GDisk®-Mini	3.9 ft (1.2 m)	2.06 MGD	4	14
GDisk®-XS	3.0 ft (0.9 m)	0.36 MGD	4	6

*at 6.5 gpm/ft²


GDisk® Operation Mode

FILTRATION




- Pass through media by gravity
- Removing Solids accumulated on the disk surface, forming a mat
- Filtered water flow through from the inside of center tube to the outlet

BACKWASH



- Operated by level switch or timer
- Low pressure suction on the front and back side of the pile cloth disk
- Non-stop filtration during backwash

SLUDGE DISCHARGE




- Sludge sediments on the bottom
- Automatic discharge of bottom sludge
- Flexible response to incoming shock load

Floating scum is evacuated into a dedicated trough for primary and wet weather application models.

Dual-Slot Backwash Manifold

- A main slot and a primary slot are provided in parallel by a partition
- Pile threads undergo delayed straightening and fluctuation while going through the primary slot. The main slot then straightens pile threads rapidly
- This patented dual-slot backwash manifold increases backwash efficiency and minimize backwash water volume



PO Box 22097
Charleston, SC 29413

843.481.4470
info@beaconh2o.com

www.beaconh2o.com

